

CM5-V Series End of Sales (KCM51VUG/KCM5XVUG/KCM5DVUG/KCM5FVUG) Enterprise NVMe™ MIXED USE SSD

The CM5-V series is a mixed-use SSD that is optimized to support a broad range of enterprise applications and associated workloads that include High Performance Computing, Online Transaction Processing, IoT and Edge Computing, Media Streaming, etc. This NVMe™ series of CM5 SSDs deliver excellent performance up to 770K random read IOPS and 165K random write IOPS, with maximum power consumption of 16 W.

Featuring KIOXIA Corporation's 64-layer BiCS FLASH™ 3D TLC memory, the CM5-V Series of enterprise NVMe™ SSDs delivers 3 DWPD (Drive Writes Per Day) of endurance and supports storage capacities up to 6.4 TB, making them ideally suited for read and write mixed-use enterprise applications.



Product image may differ from the actual product.

Key Features

- PCIe® Gen3 x4 interface single/dual port support
- NVMe™ Rev. 1.3a compliant
- Capacities from 800 GB to 6.4 TB
- Up to 770K random read IOPS in single port (1x4) mode
- Low power consumption, with 16 W maximum
- 2.5 inch small form factor, 15 mm Z-Height
- 3 DWPD with 100% random write workload
- Power loss protection and end-to-end data protection, including T10 DIF
- Sanitize Instant Erase (SIE) option^[1, 4]
- Self-encrypting drive (SED) option^[2, 4]
- Self-encrypting drive (SED), FIPS 140-2 option^[2, 3, 4]
- 5-year limited warranty

Key Applications

- High performance computing (HPC) (financial trading, healthcare, and oil/gas exploration)
- Online transaction processing (OLTP) (transactional and relational databases)
- High-frequency trading (HFT)
- IoT, IIoT and Edge computing (automotive, autonomous vehicles, transportation, smart cities and smart factories)
- Media streaming (media and entertainment, and video surveillance)

Specifications

Model Number	KCM51VUG6T40	KCM51VUG3T20	KCM51VUG1T60	KCM51VUG800G
SIE Model Number	KCM5XVUG6T40	KCM5XVUG3T20	KCM5XVUG1T60	KCM5XVUG800G
SED Model Number	KCM5DVUG6T40	KCM5DVUG3T20	KCM5DVUG1T60	KCM5DVUG800G
SED FIPS Model Number	KCM5FVUG6T40	KCM5FVUG3T20	KCM5FVUG1T60	KCM5FVUG800G
Physical				
Capacity	6,400 GB	3,200 GB	1,600 GB	800 GB
Interface	PCIe® Gen3 x4 ; NVMe™ Rev. 1.3a			
Interface Speed	32 GT/s (Gen3 x4)			
Memory Type	BiCS FLASH™ TLC			

Specifications (Continued)

Capacity	6,400 GB	3,200 GB	1,600 GB	800 GB
Performance in single port (1x4) mode(Up to)				
Sustained 128 KiB Sequential Read	3,350 MB/s		3,250 MB/s	
Sustained 128 KiB Sequential Write	3,040 MB/s		2,460 MB/s	1,250 MB/s
Sustained 4 KiB Random Read	770K IOPS	750K IOPS	650K IOPS	370K IOPS
Sustained 4 KiB Random Write	165K IOPS	160K IOPS	145K IOPS	95K IOPS
Power Requirements				
Supply Voltage	12 V ± 10 % 3.3 Vaux ± 15 %			
Power Consumption (Ready)	6.0 W Typ.			
Reliability				
MTTF	2,500,000 hours			
DWPD	3			
Warranty	5 years			
Mechanical				
Height	15.0 mm + 0, -0.5 mm			
Width	69.85 ± 0.25 mm			
Length	100.45 mm Max			
Weight	130 g Max.			
Environmental				
Temperature (Operating)	0 °C to 60 °C			
Humidity (Operating)	5 % to 95 % R.H.			
Vibration (Operating)	21.27 m/s ² { 2.17 Grms } (5 to 800 Hz)			
Shock (Operating)	9,800 m/s ² { 1,000 G } (0.5 ms duration)			

Definition of capacity: KIOXIA Corporation defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2³⁰ = 1,073,741,824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

GT/s: Giga Transfers per second.

A kibibyte (KiB) means 2¹⁰, or 1,024 bytes.

MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

DWPD: Drive Write Per Day. One drive write per day means the drive can be written and re-written to full capacity once a day every day for five years, over the stated product warranty period. Actual results may vary due to system configuration, usage and other factors.

Read and write performances may vary depending on the host device, read and write conditions, and file size.

IOPS: Input Output Per Second (or the number of I/O operations per second).

[1] The Sanitize Instant Erase (SIE) option supports Crypto Erase, which is a standardized feature defined by NVMe Express Inc.

[2] SED (Self-Encrypting Drive) supports TCG Opal SSC. Unsupported features are included in these series. For more details, please make inquiries through "Contact us" in each region's website, <https://business.kioxia.com/>

[3] FIPS drives are designed to comply with FIPS 140-2 Level 2, which defines security requirements for cryptographic module by NIST (National Institute of Standards and Technology). For the latest validation status of each model, please contact us above.

[4] Optional security feature compliant drives are not available in all countries due to export and local regulations.

*PCIe® is a registered trademark of PCI-SIG.

*NVMe™ is a trademark of NVMe Express, Inc.

*All company names, product names and service names may be trademarks of their respective companies